



55" UltraHD LED LCD Smart TV

S55UV16B-AU



QUICK REFERENCE GUIDE

Thank you for purchasing the unit.
Your unit integrates digital and analog tuner in the same unit.

Thanks for purchasing the unit. Your unit integrates digital and analog tuner in the same unit. You can enjoy both digital and analog broadcasting under following set-up easily.

The latest news, software, utility, driver, product, manual and Q&A will be found at SONIQ website.


[Http://www.soniq.com](http://www.soniq.com)

Stand Installation

Before performing work, please lay the TV on the stand to prevent it from being damaged.

Fix the stand and the unit together with screws. To remove the stand, reverse instruction as above


Black Screws:Ø4- BM(X4)




UNIT




STAND




Screws:Ø4- BM(X4)



Insert the base into the installation hole




Screws:Ø4- BM(X4)



Installation finished

Antenna Connection


Your simply connect outdoor antenna to ANT IN to receive broadcasting signals.



Power On the Unit

Connect the Power Cord to the Power Outlet. Press the POWER Button on the Remote Control or STANDBY Button on the unit to turn on the TV.

POWER Button



Remote Control


Front Side of TV

TV Auto Scan

You can perform Analog TV Auto Search Program at below methods.


Method 1:

1. Initial Setup window will be appeared when you first start to use.
2. Press ◀ / ▶ button to select the Country, then press OK Button to proceed.
3. Press ▲ / ▼ button to select your location, and then press OK button to proceed.
4. Use ▲ / ▼ button to select the tuning type, press OK for channel tuning.
5. Press ▲ / ▼ button to select the setting mode you want ,then press OK to start channel tuning.



Method 2:


Press **SOURCE** Button to display the Source list
Press **▲ / ▼** button to select **ATV** and
Press **OK** button to confirm.



Press **MENU** Button to enter the **CHANNEL** page as follows:


1. Auto Tuning will be highlighted by entering this screen. Press to continue.
2. Press **◀ / ▶** button to select country, press **OK** Button to continue.
3. Use **▲ / ▼** button to select your location, then press **OK** button to enter the next step.

4. Press ▲ / ▼ button to select tuning type, press OK to channel tuning.
5. Press OK to start auto search.



For specific operation instruction, please refer to the Instruction Manual.


1. Press HOME button to visit the HOME page.
2. Select the Instruction Manual at the bottom of the application menu. Press OK button to view the Instr uction Manual.



Package Contents



1pc Main Unit



2pc Stand

1pc Remote Control
AAA Batteries(x2)

Screws:Ø4- BM(X4)

1pc Warranty
Card1pc Quick
Installation

Specification

Supported PC Input Signal

Your unit can use as PC monitor, it supports below.

RGB-PC, HDMI/DVI-PC mode INPUT SPEC				
PC/HDMI/1/2 input				
INPUT FORMAT	Resolution	Horizontal Frequency (KHz)	Vertical Frequency (Hz)	Standard
	640 X 480	31.5	60	VGA
	640 X 480	37.861	72.809	VESA
	640 X 480	37.5	75	VESA
	720 X 400	31.5	70	VGA-T
	800 X 600	37.9	60	VESA Guidelines
	800 X 600	48.077	72.19	VESA
	800 X 600	46.9	75	VESA
	832 X 624	49.7	75	Mac
	1024 X 768	48.4	60	VESA Guidelines
	1024 X 768	60	75	VESA
	1125 X 870	68.68	75	Mac
	1280 X 800	47.8	59.8	
	1280 X 960	60.0	60	VESA
	1360 X 768	47.7	60	VESA
	1280 X 1024	63.595	60	VESA
	1440 X 900	55.9	59.9	VESA
	1680 X 1050	65.3	60	
	1920 X 1080 (RGB-PC)	66.587	59.93	VESA
	1920 X 1080 (HDMI-PC)	67.5	60	VESA
	3840 X 2160 (HDMI-PC)	67.5	30	

Power Source	~220-240V AC, 50Hz	
Power Consumption	160W	
Video Format Supporting	Y/Pb/Pr	480i, 480p, 576i, 576p, 720p (50/60Hz) 1080i (50/60Hz), 1080p (50/60Hz)
	HDMI	480p, 576p, 720p (50/60Hz), 1080i (50/60Hz), 1080p (23.97/24/25/29.97/50/59.94/60Hz) 3840 x 2160P (30Hz)
Analog TV	TV System	PAL B/G;D/K;I
Digital TV	Programme Coverage	VHF 06 to 12 UHF 27 to 69
	Video Decode	1080i ,720p ,576p,576i
	Audio	MPEG,AC3
Panel Spec	Display Area HxV(mm)	1209.600(H) x 680.400 (V)
	Panel Native Resolution	3840 x 2160 pixels
	Brightness	210cd/m ² Typ
	Contrast Ratio	4000:1 Typ
	Color Depth	1.07 B (Dithered 10bit)
Input/Output	ANT IN	ANT IN x 1
	HDMI IN	HDMI X 2
	USB IN	USB X 2 (one for USB3.0)
	VGA IN	VGA X 1
	VGA AUDIO IN	VGA AUDIO X 1
	Composite In (AV)	AV X 1
	Component In (Y/Pb/Pr)	Y/Pb/Pr X 1
	Digital Audio Out (Optical)	Digital Audio Optical Out x 1
	LAN	RJ45 x 1
	Micro SD	Micro SD X 1
Wireless LAN Specification	Standard	IEEE802.11 802.11b/g/n
	Frequency Band	2.4~2.4835 GHz ISM Band
	Output Power	<13dBm @11n,<18dBm @11b,<14dBm @11g
Audio Power	8W + 8W	
Unit Dimension	1340(L)x175(W)x816(H)mm	